

SAFETY DATA SHEET

Version 8.3
Revision Date 21.08.2021
Print Date 30.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : 2-Methylbutane Practical
Product Number : MX0760
Brand : Millipore
Index-No. : 601-006-00-1
CAS-No. : 78-78-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

1.3 Details of the supplier of the safety data sheet

Company : SIGMA-ALDRICH CANADA LTD.
2149 WINSTON PARK DRIVE
OAKVILLE ON L6H 6J8
CANADA
Telephone : +1 905 829-9500
Fax : +1 905 829-9292

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA)
+1-703-527-3887 CHEMTREC
(International)
24 Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)**

Flammable liquids (Category 1), H224
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Aspiration hazard (Category 1), H304
Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

| | |
|----------------------------|---|
| Hazard statement(s) | |
| H224 | Extremely flammable liquid and vapor. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |
| Precautionary statement(s) | |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground and bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 | Use non-sparking tools. |
| P243 | Take action to prevent static discharges. |
| P261 | Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/ doctor. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. |
| P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. |
| P331 | Do NOT induce vomiting. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |
| P391 | Collect spillage. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

- none

SECTION 3: Composition/information on ingredients

3.1 Substances

| | |
|------------------|----------------|
| Formula | : C5H12 |
| Molecular weight | : 72.15 g/mol |
| CAS-No. | : 78-78-4 |
| EC-No. | : 201-142-8 |
| Index-No. | : 601-006-00-1 |

| Component | Classification | Concentration * |
|-------------------|--|-----------------|
| isopentane | | |
| | Flam. Liq. 1; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H224, H336, | <= 100 % |

| | | |
|------------|------------|--|
| | H304, H411 | |
| * Weight % | | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities**Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Components with workplace control parameters**

| Components | CAS-No. | Value | Control parameters | Basis |
|------------|---------|-------|--------------------|-------|
|------------|---------|-------|--------------------|-------|

| | | | | |
|------------|---------|-------|------------------------------------|---|
| isopentane | 78-78-4 | TWA | 600 ppm 1,770 mg/m ³ | Canada. Alberta, Occupational Health and Safety Code (table 2: OEL) |
| | | TWAEV | 1,000 ppm | Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants |
| | | TWA | 1,000 ppm | Canada. British Columbia OEL |
| | | TWA | 1,000 ppm | USA. ACGIH Threshold Limit Values (TLV) |

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm

Break through time: 60 min

Material tested: KCL 720 Camapren®

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| a) Appearance | Form: liquid Color: colorless |
| b) Odor | No data available |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point: -159.77 °C (-255.59 °F) - (ECHA) |
| f) Initial boiling point and boiling range | 30 °C 86 °F at 1,013 hPa |
| g) Flash point | -51 °C (-60 °F) - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 7.6 %(V) Lower explosion limit: 1.4 %(V) |
| k) Vapor pressure | 769.92 hPa at 20 °C (68 °F) |
| l) Vapor density | 2.49 - (Air = 1.0) |
| m) Density | 0.62 g/cm ³ at 20 °C (68 °F) |
| Relative density | No data available |
| n) Water solubility | 0.049 g/l at 25 °C (77 °F) - slightly soluble |
| o) Partition coefficient: n-octanol/water | log Pow: 4.00 at 25 °C (77 °F) - A remarkable bioaccumulation potential is expected (log Po/w >3). |
| p) Autoignition temperature | 420 °C (788 °F) at 1,013 hPa |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | none |

9.2 Other safety information

| | |
|------------------------|--------------------|
| Relative vapor density | 2.49 - (Air = 1.0) |
|------------------------|--------------------|

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:
Oxidizing agents

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 2,000 mg/kg
(OECD Test Guideline 401)

Remarks: No mortality observed at this dose.

LC50 Inhalation - Rat - male and female - 4 h - 62.19 mg/l

Remarks: (ECHA)

Dermal: absorption

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Test system: *S. typhimurium*

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Remarks: (ECHA)

Test Type: Micronucleus test
Species: Rat
Cell type: Bone marrow
Application Route: inhalation (vapor)
Method: Mutagenicity (micronucleus test)
Result: negative
Remarks: (ECHA)

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d
Result: 71.43 % - Readily biodegradable.
(OECD Test Guideline 301F)
Remarks: (ECHA)

12.3 Bioaccumulative potential

Bioaccumulation Pimephales promelas (fathead minnow)(isopentane)

Bioconcentration factor (BCF): 171

Remarks: Does not significantly accumulate in organisms.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Discharge into the environment must be avoided.

Millipore - MX0760

Page 8 of 10

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

TDG

UN number: 1265 Class: 3 Packing group: I
Proper shipping name: PENTANES
Labels: 3
ERG Code: 128
Marine pollutant: no

IMDG

UN number: 1265 Class: 3 Packing group: I EMS-No: F-E, S-D
Proper shipping name: PENTANES
Marine pollutant : yes

IATA

UN number: 1265 Class: 3 Packing group: I
Proper shipping name: Pentanes

SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the

information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.3

Revision Date: 21.08.2021

Print Date: 30.06.2023